

**TECHNICAL DATA SHEET**

**DELTA®-ADHESIVE**

**Emulsion Adhesive for Self-adhering Membranes**

**DESCRIPTION**

DELTA®-ADHESIVE is a rubber-based adhesive for cold weather application self-adhering membranes such as DELTA®-VENT SA.

**FEATURES**

- Quick-setting
- Aggressive tack provides increased adhesion of membrane
- Suitable for application at normal and low temperatures
- Easily applied

**USES**

Used as an adhesive to increase bond strength of self-adhering membrane such as DELTA®-VENT SA when applied to masonry, concrete, exterior grade gypsum board and metal surfaces.

DELTA®-ADHESIVE is the product of choice on above grade applications of self-adhered membranes where a quick setting, aggressive tack is required. Designed for cold weather applications above -12°C (10°F).

Important: apply a thin coat only.

**LIMITATIONS**

Avoid direct application on polystyrene material. Avoid use and exposure to open flames, electrical discharges and other ignition sources or where solvent odors may taint food or other susceptible products.

**PREPARATION**

Surfaces must be dry and free from dust, dirt, grease, oil, ice or other foreign matter.

**APPLICATION**

DELTA®-ADHESIVE is applied by brush or roller. Rollers should have a heavy nap of natural material such as lamb's wool. Dry 30 minutes before applying membrane, longer under cold conditions. Coated surfaces not covered by membrane during the working day must be re-coated.

**CLEAN UP**

Use mineral spirits. Clean hands with a waterless hand cleaner.

**CAUTION**

Contains extremely flammable solvents. Take suitable fire precautions. Do not allow smoking or welding in working area. Keep away from open flame or spark. Use under well ventilated conditions. Avoid prolonged breathing of vapors and avoid contact with skin. Excessive inhalation of vapors can cause dizziness. Use respirator approved for organic vapor. Keep containers covered when not in use. Harmful if swallowed.

**Technical Data**

Product name	DELTA®-ADHESIVE
Color	Blue
Solids by volume	approx. 35%
Weight	approx. 0.919 kg/L (7.67 lbs/gal)
Application temperature	-12°C (10°F) to 40°C (104°F)
Coverage	Up to 8.2 m <sup>2</sup> /l (350 ft <sup>2</sup> /gal.) depending on porosity and texture of surface.
Drying time	Initial set: 30 minutes Set through: 2 hours
Service temperature	-40°C (-40°F) to 70°C (150°F)
Flammability	Wet: Flammable Dry: Burns
Packaging	17L (4.49 gal.) per pail
Suitable for use with (cold weather)	DELTA®-VENT SA



DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit [www.dorken.com](http://www.dorken.com).