

TECHNICAL DATA SHEET

DELTA®-SEALANT

MATERIAL

Elastic sealing compound suitable for use with DELTA® foundation protection membranes.

- Quick-setting
- Aggressive tack provides increased adhesion.
- Adheres to:
 - Concrete
 - CMU
 - Masonry
 - Preserved wood foundations

DELTA®-SEALANT is a black mastic formulation that is used to seal the flat tab and overlaps between membranes during the installation process. The sealant is also used to seal any gaps in the membrane created at interior and exterior corner installations where a tight fit may not be possible.

DELTA®-SEALANT is used in combination with DELTA®-MS and DELTA®-DRAIN to ensure a complete and water-tight system.

Technical Data

Product name	DELTA®-SEALANT
Color	Black
Material	Black mastic
Packaging	12 cartridges / box
Cartridge size	27.9 fl.oz (825 ml)
Coverage	approx. 15m/cartridge
Shelf life	12 months
Curing time	Skin formation after 25 minutes at 50% humidity
Application	+ 40 °F (+ 5 °C)
Temperature range	-22 °F to + 176 °F (-30 °C to + 80 °C)



DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit www.dorken.com.