

TECHNICAL DATA SHEET

DELTA®-HF PRIMER

Emulsion Primer for Self-adhering Membranes

DESCRIPTION

DELTA®-HF PRIMER is a solvent free primer for self-adhering membranes.

FEATURES

- Quick drying
- Environmentally friendly - no VOC content
- High tack provides positive initial adhesion to membrane, especially on vertical faces
- Non-flammable during application
- Easily applied by spray or roller
- Polyacrylate dispeson-based (no solvent)

USES

Used as a primer for self-adhering membranes such as DELTA®-VENT SA when applied to wood, preserved wood, polystyrene, masonry and concrete foundations. DELTA®-HF PRIMER is the primer of choice when it is necessary to achieve a fast drying, solvent free, tacky surface where walking over the surface is not required during application. This is important for the application of membranes on vertical surfaces. Designed for applications above 5°C (40°F).

LIMITATIONS

Apply under dry conditions above 5°C (40°F). Do not freeze. Store DELTA®-HF PRIMER above 0°C (32°F). Do not use if frozen.

PREPARATION

Surfaces must be dry and free from dust, dirt, grease, oil, ice or other foreign matter.

APPLICATION

Apply by roller at the coverage rate shown. Airless, air assist, or spray equipment may also be used. The product is not suitable for use with a garden-type sprayer. Pour primer from container into sprayer and spray fine mist over entire substrate. Allow primer to dry thoroughly before applying membrane. Primed surfaces not covered by membrane during the same working day must be reprimed. DELTA®-HF PRIMER is intended to be used as supplied and should not be diluted.

CLEAN UP

For uncured primer use water.

CAUTION

Harmful if swallowed.
Do not freeze.

Technical Data

Product name	DELTA®-HF PRIMER
Color	White / Clear when dry
Weight	approx. 1.0 kg/l (0.26 lbs/gal)
Application temperature	5°C (40°F) to 40°C (104°F)
Coverage	Up to 23 m ² /l (250 ft ² /0.26 gal.) depending on porosity and texture of surface.
Drying time	@ 50% R.H. 20°C (68°F) dry substrate: Initial set: 10 minutes
Service temperature	5°C (40°F) to 70°C (150°F)
Flammability	Wet: Non-flammable
Packaging	5 l (1.3 gal.) per pail
Suitable for use with	DELTA®-VENT SA

DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit www.dorken.com.