

TOP 10 REASONS TO USE DELTA®-VENT SA

Sprays and bitumen sheets may not provide enough protection due to uneven application and low vapor permeability, causing mold and long-term water damage. That's why you need **DELTA®-VENT SA**.

- 10 **SELF-ADHERING AIR AND MOISTURE BARRIER**
- 9 **BEST TECHNICAL SUPPORT IN THE INDUSTRY**
- 8 **EXCLUSIVE SELF-ADHERING EDGE LAP**
- 7 **INDUSTRY-LEADING PERMEABILITY (50 PERMS)**
- 6 **ACCESSORIES SEAL EVERY CORNER, EDGE, AND GAP**
- 5 **ACCEPTED BY HEALTH PRODUCT DECLARATION® COLLABORATIVE FOR LEED® v4 BUILDINGS**
- 4 **ABAA APPROVED, AC 38-ICC ESR 2932, ASTM E2357, RED LIST COMPLIANT**
- 3 **FLOW-THROUGH ASSEMBLY ALLOWS VAPOR TO ESCAPE WHILE MAXIMIZING AIR TIGHTNESS**
- 2 **LONG-TERM ADHESION ELIMINATES FASTENER LEAKS**
- 1 **SIMPLE APPLICATION HELPS ENSURE PROPER INSTALLATION**

Open-joint Cladding?

Protect the wall assembly in your open-joint cladding design from water damage with **DELTA®-FASSADE S**.

DELTA®-VENT SA helps your buildings stay dry and last longer with improved energy efficiency.